EC782 ADA LEVER



FEATURES

ADA Lever Handle

Public, Private & Remote Allocation System (RAS) mode

Key override

Up to 80,000 cycles per pair of batteries

Batteries included

Battery condition indicator

Audible keypad (can be turned on/off)

8 digit master code

6 digit sub-master code

4 digit user codes

6 digit technician code

Auto unlock mode (can be turned on/off)

Technician mode

OPTIONS

Finishes: Black (B), Silver (S), White (W), Custom* Keypad Direction: Vertical (V), Right (R), Left (L)

Push to Lock SLAM Latch (3) Remote Allocation System (RAS)

DIMENSIONS & SPECIFICATIONS

External Dimensions:

Length: 185.5mm (7.3") Width: 37mm (1.46") Depth: 28.7mm (1.13")

Mounting Hole Shape: 2 or 3 point mounting (see technical drawing)

Spindle Length: 20mm standard, 24mm by special order*


Power: 2 x AA Battery (Alkaline)

Operations: Up to 80,000 cycles per pair of AA batteries **Low Battery:** LED lights with battery condition indicator

Material: Zinc diecast Finish: Powder coated

Standard Cam Capability: 1/4" to 1 1/2"

Keys Included: 2 For Internal use



ORDERING INFORMATION

Order # for EC782 shown above is EC782SV

Order #FinishKeypad DirectionSLAM LatchRASEC782(B) Black(V) Vertical3RAS(S) Silver(P) Bight

(S) Silver (R) Right Custom* (L) Left